

KINGTOP

5G Rugged tablet Specification



Specifications

Basic configuration	Product Model	KT-KP12
	OS Version	Android™ 12.0
	CPU Type	MTK6891(MTK 1100), 6nm, 8 core, 3*Arm Cortex-A78@2.6GHz, 4*Arm Cortex-A55@2.0GHz
	Memory	6GB RAM+128GB ROM
Display	Screen	10.1" HD (1920*1200)
	Touch screen	Support (Multi-point touch)
	TP	Capacitive multi-touch screen G+FF
Network Connections	Bands	2.4G&5GHz,dual band
	Wi-Fi	Wi-Fi6 IEEE 802.11 a/b/g/n/ac/ax
	Bands	5G: N1/3/5/7/8/20/28/38/40/41/77/78/79 4G: TDD-LTE:B34/38/39/40/41; FDD-LTE:1/3/5/7/8/20/26/28A/28B;TD-SCDMA: B38/39/40/41 3G: WCDMA: B1/2/5/8; CDMA:BC0/BC1 2G: GSM: B2/3/5/8
	Data link	5G:NR 4G:TDD LTE FDD LTE 3G:HSPA+ ,EVDO, GPRS EDGE; 2G:GPRS class 12/EDGE
Camera	Front	8MP FF
	Rear	20MP AF
	Flashlight	Support

Speaker	Speaker	8R, 1W*2
	MIC	Support (Dual micro)
Sensor	G-sensor	Support(3D)
	Sensing distance	Support
	Compass	Support
Scan module	1D/2D	New World CM60/N1/, Zebra SE4710/Hoeni N6603/N6703/HS7 Compatible design for both hard and soft interfaces(optional)
	Standard	CM60
Connectivity	Bluetooth	BT5.1
	NFC	Support, 13.56MHz Contactlese interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
	OTG	Support
	GPS	GPS/A-GPS/GLONASS/BEIDOU
Interface	SIM Card Slot	Dual cards(SIM+SIM or SIM+TF)
Battery	Capacity	10000mAh Lithium-ion polymer battery
Accessories	Charger	DC 5V/3A, 9V/3A
	Data cable	TYPE-C, 3.0
	Size	252.7*171.9*13.2mm
Environment	Working Temperature	-10℃-50℃
	Storage Temperature	-20℃-70℃
	Working Humidity	5%-95%
	Waterproof	IP67

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.