

4G Rugged tablet Specification



Specifications

Basic configuration	Product Model	KT-KP12D
	OS Version	Android™ 13.0
	CPU Type	UNISOC7863,12nm,8 core
	Memory	6GB RAM+128GB ROM
Display	Screen	10.1" HD (1920*1200)
	Touch screen	Support (Multi-point touch)
	TP	Capacitive multi-touch screen G+FF
Network Connections	Bands	2.4G&5GHz,dual band
	Wi-Fi	Wi-Fi5, IEEE 802.11 a/b/g/n/ac
	Bands	4G: TDD-LTE:B34/38/39/40/41; FDD-LTE:1/3/5/7/8/20/26/28A/28B;TD-SCDMA: B38/39/40/41 3G: WCDMA: B1/2/5/8; CDMA:BC0/BC1 2G: GSM: B2/3/5/8
	Data link	4G:TDD LTE FDD LTE 3G:HSPA+ ,EVDO , GPRS EDGE; 2G:GPRS class 12/EDGE
Camera	Front	8MP FF
	Rear	13MP AF
	Flashlight	Support
Speaker	Speaker	8R, 1W*2
	MIC	Support (Dual micro)
Sensor	G-sensor	Support(3D)
	Light sensing	Support
	Compass	Support
	Motor	Support
	Fingerprint unlock	Support
	GPS	GPS/A-GPS/GLONASS/BEIDOU
Scan module	1D/2D	CM60 standard
Connectivity	Bluetooth	BT5.0
	NFC	Support, 13.56MHz Contactless interface modem - ISO/IEC 18000-3 、 18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
	OTG	Support
Interface	SIM Card Slot	Dual cards(SIM+SIM or SIM+TF)
	USB interface	TYPE-C, OTG
	Earphone interface	3.5mm

Battery	Capacity	8500mAh/3.8v
Others	Charger	DC 9V/2A
	Data cable	TYPE-C, 2.0
	Dimension	254.2*172.6*13.5mm
	Weight	830g
	FM	Support
	Button	5 physical buttons: Volume key+-, OnOff key, Custom key 1, Custom key 2
	Indicator	Red: charging; Green: fully charged
	Google CMS	Support
Environment	Working Temperature	-10℃-50℃
	Storage Temperature	-20℃-70℃
	Working Humidity	5%-95%
	Waterproof	IP67
	Explosion proof grade	Compatible Ex ib IIC T4 Gb

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.