



Specifications

| | | |
|---------------------|---------------------------------|---|
| Basic configuration | Product Model | KT-KP18-4G |
| | CPU | MTK6762, Octa-core 2.0Ghz / MTK6761, Quad-core 2.0Ghz |
| | OS Version | Android™ 12.0 |
| | Memory | 4GB RAM+64GB ROM(MTK6762)/ 3GB RAM+32GB ROM(MTK6761) |
| | TF card | Support |
| | GPS | Support GPS L1+L5/ Beidou L1+III B2A/Galileo L1+Ea5 /GLONASS/AGPS |
| | WLAN | Support 2.4/5GHz dual-band WIFI Support 802.11ac, Wi-Fi 5 |
| | Bluetooth | Bluetooth 5.1 |
| | 4G wireless transferring | 2G: GSM(B2/3/5/8) 3G: WCDMA (B1/2/5/8) TDS B34/39 CDMA 1X EVDO (BC0) 4G: TDD (B34/38/39/40/41) FDD (B1/2/3/5/7/8/20/26/28a&b) |
| | SIM Card type | Dual SIM Card |
| | TF card slot | Support SIM&TF |
| | Light indicator | 1. Battery level ≤ 10%: Red light flashing, adapter red light constantly on for charging 2. 10% ≤ battery level ≤ 90%: Plug-in adapter with red light constantly on for charging 3. Battery level > 90%: The green light of the adapter is constantly on for charging |
| Sensor | Ray distance | Support |
| | 3D Accelerated Gravity | Support |
| | Electronic compass(geomagnetic) | Support |
| | Gyroscope | Support |
| | NFC | Support, 13.56MHz Contactless interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance |
| Camera | Front | 5mp FF |
| | Rear | 13mp AF |
| | Flashlight | Support |
| Audio | Speaker | Single speaker 8Ω, 0.8W (MAX:1W) |
| | Headphone | 1506 waterproof headphone |
| | Motor | 0827 flat motor |
| | MIC | Dual MIC, 3D DNR MIC |
| IO interface | Earphone | Not support |
| | USB | Type-C USB2.0+charging, support OTG cable, 5V/3A |
| LCM | LCD | 5.7 inch IPS, HD+, 720*1440 |
| | TP | Multi-touch, IC: GT911 |
| | Cover plate material | Corning GG3, Reinforced glass cover plate, fully fitted, 1.1mm |
| Fingerprint module | Standard | Interface:SPI, Sensor: FT9371L6, up to support five fingerprints |
| Scan module | Standard | CM60 |
| | Optional | 2D: Honeywell, N6603, MIPI interface, soft decoding Zebra, SE4710, MIPI interface, soft decoding |

| | | |
|-------------|---------------------|---|
| Button | Left | Custom key * 1+volume key |
| | Right | On/Off+Custom |
| Others | Google GMS | Support |
| | SIM Card Slot | Dual cards(SIM+SIM or SIM+TF) |
| | Battery | Removable battery, 4000mAh gel polymer , 4.35V (3.8V), 10K NTC resistance |
| Accessories | Adaptor PE+ | DC 5V/2A battery charging slot *1 Overall charging slot *1 Indicator *2 |
| | Cable | Type-C USB2.0+charging, Support OTG cable, support 5V/3A |
| | Dimension | 162.5 x 77.5 x 14.6mm |
| Environment | Working Temperature | -20℃-60℃ |
| | Storage Temperature | -40℃-70℃ |
| | Working Humidity | 5%-95% |
| | Waterproof | IP67 |

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.