



Specifications

Basic configuration	Product Model	KT-KP18-5G
	CPU	MTK6877(MTK900), 6nm, 2*A78 @2.4GHz, 6*A55 @2.0GHz
	OS Version	Android™ 12.0
	Memory	4GB RAM+64GB ROM
	TF card	Support
	GPS	Support GPS L1+L5/ Beidou L1+III B2A/Galileo L1+Ea5 /GLONASS/AGPS
	WLAN	Support 2.4/5GHz dual-band WIFI Support 802.11ax Wi-Fi6
	Bluetooth	Bluetooth 5.1
	FM	Not support
	5G wireless transferring (All Netcom)	2G: GSM(B2/3/5/8) 3G: WCDMA (B1/2/5/8) CDMA 1X EVDO (BC0) 4G: TDD (B34/38/39/40/41) FDD (B1/2/3/5/7/8/20/28a&b) 5G: NR (N1/3/8/28/38/41/77/78/79)
	SIM Card type	5G Single NANO SIM card
	TF card slot	Support (SIM/TF optional)
	eSIM	Not support
Light indicator	1. Battery level ≤ 10%: Red light flashing, adapter red light constantly on for charging 2. 10% ≤ battery level ≤ 90%: Plug-in adapter with red light constantly on for charging 3. Battery level > 90%: The green light of the adapter is constantly on for charging	
LCM	LCD	5.7 inch IPS, HD+, 720*1440
	TP	Multi-touch, IC: GT911
	Cover plate material	Corning GG3, Reinforced glass cover plate, fully fitted, 1.1mm
Sensor	Ray distance	Support
	3D Accelerated Gravity	Support
	Electronic compass(geomagnetic)	Support
	Gyroscope	Support
	Barometric altitude	Not support
	NFC	Support, 13.56MHz Contactless interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
Camera	Front	5mp FF
	Rear	13mp AF
	Flashlight	Support
Audio	Speaker	Single speaker 8Ω, 0.8W (MAX:1W)
	Headphone	1506 waterproof headphone
	Motor	0827 flat motor
	MIC	Dual MIC, 3D DNR MIC
IO interface	Earphone	Not support
	USB	Type-C USB2.0+charging, support OTG cable, 5V/3A

Fingerprint module	Standard	Interface:SPI, Sensor: FT9371L6, up to support five fingerprints
Scan module	Standard	CM60
	Optional	2D: Honeywell, N6603, MIPI interface, soft decoding Zebra, SE4710, MIPI interface, soft decoding
Button	Left	Custom key * 1+volume key
	Right	On/Off+Custom
Others	Google GMS	Support
	SIM Card Slot	Dual cards(SIM+SIM or SIM+TF)
	Battery	Removable battery, 4000mAh gel polymer , 4.35V (3.8V), 10K NTC resistance
Accessories	Adaptor PE+	DC 5V/2A battery charging slot *1 Overall charging slot *1 Indicator *2
	Cable	Type-C USB2.0+charging, Support OTG cable, support 5V/3A
	Dimension	162.5 x 77.5 x 14.6mm
Environment	Working Temperature	-20℃-60℃
	Storage Temperature	-40℃-70℃
	Working Humidity	5%-95%
	Waterproof	IP67

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.