

5G Handheld Computer Specification



Specifications

Basic configuration	Product Model	KT-KP26-5G
	CPU	MT6877(MTK900), 6nm, Octa core 2*A78 @2.4GHz, 6*A55 @2.0GHz
	OS Version	Android™ 11.0
	RAM	6GB
	ROM	128GB
	5G wireless transferring (All Netcom)	5G: N1/N3/N8/N38/N41/N77/N78/N79/N28AB GSM: 2/3/5/8 WCDMA: 1/2/5/8 TDS: 34/39 (compatible) TDD: 34/38/39/40/41 FDD: 1/2/3/5/7/8/20/26/28AB
LCM	LCD-1	6.217 inch (IPS), HD+, 720*1520
	TP	Cover plate: Corning GC3, fully fitted, 1.1mm, with AF anti fingerprint oil G+FF process, support glove touch
Camera	Front	5mp/8mp(optional)
	Rear	13mp/48mp(optional)
	Rear secondary camera	5mp FF
	Flashlight	Support(red/green/blue)
Chip carrier	SIM card	Support, NANO card (optional)
	TF card	Support, up to 256GB
Wireless data	Data link	5G:NR 4G:TDD LTE FDD LTE 3G:HSPA+, EVDO, GPRS EDGE; 2G:GPRS class 12/EDGE
	Wi-Fi	2.4G/5G/WIFI6: LAN 802.11 ax/ac/a/b/g/n
	GPS	GPS/Beidou/Galileo/GLONASS/AGPS
	Bluetooth	Bluetooth 5.1
	FM	Not Support

	NFC	Support 13.56MHz - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
IO interface	USB interface	Support TYPE-C, 5V/3A, 3.0USB, 24PIN, OTG
	Fingerprint	Support(Up to five fingerprints)
	Cradle	Support
	SIM Card Slot	Dual cards(SIM+SIM or SIM+TF)
Sensor	Light/Distance	Support
	3D Accelerated Gravity	Support
	Geomagnetism	Support
	Gyroscope	Support
	Altitude pressure	Support
Scan module	Standard	CM60
	Compatible	Honey N6703/N4703/HS7, Zebra SE4710
Audio	Speaker	1W power 8 Ω * 2, 1217 dual speaker
	Motor	Support
	MIC	Adopting digital MIC and IG1202 noise reduction chip, the noise reduction mode can be turned on and off
Button	Left	Scan button * 1
	Right	Power on button * 1, Volume+- button * 1, Scan button * 1
Others	Google GMS	Support
	Battery	Removable battery, 5000mAh gel polymer , 4.35V (3.8V), 10K NTC resistance
Accessories	Adaptor PE+	Type: APS-KI015W-G Input: AC:100-240V 50/60HZ 0.5A MAX Output: DC:5V/7V/9V--1.57A, 12V--1.25A
	Cable	TYPE-C: 7.8mm, Total length: 0.8m, 5V/2A, Black
	Dimension	168.3 x 79.5 x 16.9mm
Environment	Working Temperature	-20℃-60℃
	Storage Temperature	-40℃-70℃
	Working Humidity	5%-95%
	Waterproof	IP67

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.