

4G Handheld Computer Specification



Specifications

Basic configuration	Product Model	KT-KP36
	CPU	MTK6762, 8 core, 2.0GHz, 12nm
	OS Version OS	Android™ 11
	RAM	4GB
	ROM	64GB
	Wireless transferring (All Netcom)	2G: B2/B3/B5/B8 3G: WCDMA: B1/B5/B8, CDMA BC0, TD-SCDMA: B34/B39 4G: FDD-LTE: B1/B3/B5/B7/B8/B20, TDD-LTE: B34/B38/B39/B40/B41
LCM	LCD	4 inch IPS, HD+, 800*480
	TP	Industrial grade capacitive screen
	Cover plate material	Corning GG3, Reinforced glass cover plate
Camera	Front	MIPI interface, Mega pixel: 5M FF fixed, IC: GC5035
	Rear	MIPI interface, Mega pixel: 13M AF, IC: SK53L8
	Flashlight	Support
	Indicator	Support
Cardholder	SIM card	Support NANO card
	PSAM card	Support
	TF card	Support up to 256G
Wireless data	Data link	4G: TDD LTE FDD LTE 3G: HSPA+ ,EVDO, GPRS EDGE; 2G: GPRS class 12/EDGE
	Wi-Fi	2.4G/5G a/b/g/n/ ac
	GPS	GPS/Beidou/Galileo/GLONASS/AGPS
	Bluetooth	BT 5.0
	FM	Support
	NFC	Support, 13.56MHz - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance

IO interface	USB interface	Support TYPE-C, 5V/3A Charging, 2.0USB, Support OTG, Support headset function
	External data interface	Support Scan key
	Cradle	Support
Sensor	Light/Distance	Support
	3D Accelerated Gravity	Support
	Geomagnetism	Support
	Gyroscope	Support
	Altitude pressure	Support
Scan module	Standard	CM60
	Long-range scanner	TBD
	Compatible	Honeywell N6703/N4703, ZebraSE4710/4750
Audio	Power amplifier	K-type
	Speaker	2W power, IP68 waterproof
	Receiver	0809 Waterproof handset
	Motor	1027 Flat motors
	MIC	Dual microphones
Button	Physical Button	Total 34 keys, front keys*29, side scan keys*2, side PTT keys*1, volume ± keys*2
Power	PE+ 2.0	TYPE-C 5V/3A 15W
Battery	Main battery (removable)	5000mAh gel polymer battery, 4.35V (3.8V), 10K NTC resistance
Module	ID card module	Support
	Printer module	Support
	Beidou module	Support
	Explosion proof design	Support
Accessories	Adaptor PE+	Type: APS-KI015W-G Input: AC:100-240V 50/60HZ 0.5A MAX Output: DC:5V/7V/9V--1.57A, 12V--1.25A
	Cable	TYPE-C: 7.8mm, Total length: 0.8m, 5V/2A, Black
	Earphone	TYPE-C
	Dimension	165 x 65 x 15mm
Environment	Working Temperature	-20°C-60°C
	Storage Temperature	-40°C-70°C
	Working Humidity	5%-95%
	Waterproof	IP65(1.5M free drop)

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.