



Specifications

Basic configuration	Product Model	KT-KP58
	CPU	MTK6765, Octa-core 2.0Ghz
	OS Version	Android14.0
	Memory	4GB RAM+64GB ROM
	TF card	Support TF card(up to 128GB)
	Bluetooth	Bluetooth 5.0
LCM	LCD	5.45 inch (IPS), HD+, 1440*720
	TP	Capacitive multi touch screen,Corning 3rd cover
Network	WLAN	Support 2.4/5GHz dual-band WIFI Support 802.11ac, Wi-Fi 5
	Cellular data	4G:TDD LTE FDD LTE 3G:HSPA+ ,EVDO, GPRS EDGE; 2G:GPRS class 12/EDGE
Sensor	GNSS	GPS/Beidou/Galileo/GLONASS/AGPS
	Motion Sensor	3-axis Accelerometer with MEMS Gyro
	Light Sensor	Automatically adjusts display backlight brightness
	NFC	Support, 13.56MHz Contactless interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance only MTK6762 support
Camera	Front	5mp FF
	Rear	13mp AF
	Flashlight	Support
Audio	Speaker	Power: 1W*1 8Ω 95dB
	Receiver	Support
	Motor	Support
	MIC	Dual MIC,Main MIC+ 3D DNR MIC
IO interface	Earphone	Not support
	USB	Type-C USB2.0+charging, support OTG cable, 5V/2A
	SIM Card type	Dual cards(SIM+SIM or SIM+TF)
	TF card slot	Support TF card(up to 256GB)
Data Capture	Fingerprint module	Not support
	Scan module	T20/CM60E(Optional), support 1D/2D code
	Scan angle	Horizontal 42°, Vertical 28°
	Support code	PDF417, QR Code, DataMatrix, AZTEC,Hanxin code, Maxicode, Micro QR, Micro PDF417, Composite, etc.EAN13, EAN8, UPCA, UPCE, Code 128, Code 39, Codabar, UCC/EAN128, RSS,ITF, ITF14, ITF6, ISSN, ISBN, Standard 25, Matrix 25,Industrial 25,Plessey, MSI Plessey, Code 11, Code 93, etc.
Others	Button	Right side: scan button*1, power button *1,custom button *1side; Left side: scan button*1, volume +/- button*1
	Google GMS	Support
	Battery	Removable battery, 5000mAh gel polymer, 4.35V (3.8V)
	Dimension	157.2 x 77.4 x 15.5mm
	Weight	≥280g
	Certifications	3C certification

Accessories	Adaptor PE+	DC 5V/2A, 9V2A 33W flash charge
	Cable	Type-C USB2.0+charging
	Wrist strap	Optional
	Cradle	Optional
Environment	Operating Temperature	-20℃-60℃
	Storage Temperature	-40℃-70℃
	Working Humidity	5%-95%
	Drop Specifications	Multiple 1.5 m drops to tile over concrete
	Sealing	IP65

Shenzhen Jintaiyi Electronic Co., Ltd.
12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051
Email: info@kingtoptec.com
<https://www.kingtoptec.com/>
Copyrights © 2023 Kingtop Corp. All Rights Reserved
**Product specifications and availability are subject to change without notice.*