



Specifications

Basic configuration	Product Model	KT-KP68
	CPU	MediaTek 5G Octa Core 2*2.4GHz A78 6*2.0GHz A55
	OS Version	Android14.0
	Memory	6GB RAM+128GB ROM
	Bluetooth	Bluetooth 5.1
LCM	LCD	6.517 inch (IPS), HD+, 720*1600
	TP	5-point capacitive touch screen, American Corning Three Dynasty tempered glass, Support gloves touch
Network	WLAN	Support 2.4/5GHz dual-band WIFI LAN 802.11 ax/ac/a/b/g/n, Wi-Fi 6
	Cellular data	5G:NSA/SA 4G:TDD LTE FDD LTE 3G:HSPA+ GPRS EDGE; 2G:GPRS Class 12/EDGE
Sensor	GNSS	GPS+Glonass+Beidou+Galileo L1+L5
	Motion Sensor	3-axis Accelerometer with MEMS Gyro
	Magnetometer	eCompass automatically detects direction and orientation
	Light Sensor	Automatically adjusts display backlight brightness
	NFC	Support, 13.56MHz Contactless interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
Camera	Front	8mp FF
	Rear	16mp AF
	Rear secondary camera	5mp FF
	Flashlight	Support 800mHA
Audio	Speaker	1W 8Ω*2
	Headphone	Support 0809 IP68 waterproof
	Motor	Flat motor
	MIC	Dual MIC, 3D DNR MIC
IO interface	Earphone	Not support
	USB	Type-C USB2.0+charging, support OTG cable, 5V/2A
	SIM Card type	Dual cards(SIM+SIM or SIM+TF)
	TF card slot	Support TF card(up to 256GB)
Data Capture	Fingerprint module	Supuport fingerprint unlock
	Scan module	Newland CM60, support 1D/2D code
	Ray distance	Scanning distance up to 60cm/1.968 foot
	Support code system	PDF417, QR Code, DataMatrix, AZTEC, hanxin code, Maxicode, Micro QR, Micro PDF417, Composite, etc.EAN13, EAN8, UPCA, UPCE, Code 128, Code 39, Codabar, UCC/EAN128, RSS,ITF, ITF14, ITF6, ISSN, ISBN, Standard 25, Matrix 25,Industrial 25,Plessey, MSI Plessey, Code 11, Code 93, etc.
Button	Left	2* Scan button, 1*Function button
	Right	1* Power button, 1*Volume +/- button
Others	Google GMS	Support
	Battery	Removable battery, 5500mAh gel polymer
	Dimension	172 x 78 x 15.4mm

	Certifications	3C certification, Drop test report,RoHS report
Accessories	Adaptor PE+	65W Fast charger*1
	Cable	Type-C USB2.0+charging
	Wrist strap	Optional
	Cradle	Optional
	Protect Shell	Optional
	Charging cradle	Optional
Environment	Operating Temperature	-20℃-55℃
	Storage Temperature	-40℃-70℃
	Working Humidity	5%-95%
	Drop Specifications	Multiple 1.5 m drops to tile over concrete
	Sealing	IP67

Shenzhen Jintaiyi Electronic Co., Ltd.
12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051
Email: info@kingtoptec.com
<https://www.kingtoptec.com/>
Copyrights © 2023 Kingtop Corp. All Rights Reserved
[*Product specifications and availability are subject to change without notice.](#)