

# 5G Mobile Hotspots Specification



## Specifications

Basic configuration	Product Model	<b>KT-M2A</b>
	OS Version	Android™ 11.0
	Chipset	MTK MT6833/MT6877, 7nm 2*A76 (2.0GHz) +6*A55 (2.0GHz), GPU: Mali Natt MC2
	Memory	LPDDR4X 2GB RAM+EMMC 16GB ROM
	WiFi	MT6631
	BT	Bluetooth 5.1(optional)
LCM	LCD	2.4"TFT MIPI (LCD or LED)
	TP	Support
LED	LED	Red, Green, Blue
Cellular	Protocal	3GPP Rel.15, 5G NR, SA/NSA, Sub 6G/LTE Category 13
	Bands	5G NR:n2/n5/n12/n25/n66/n41/n48/n77/n78 4G:B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B29/B30/B41/B66
	Throughput	NR: Downlink/Uplink up to 2.77Gbps/1.25Gbps LTE: Downlink/Uplink up to 391Mbps/150Mbps
	Antenna	4*4 MIMO
WiFi	Bands	2.4G, 5.8G, DBSC
	Protocal	802.11 a/b/g/n/ac
	Throughput	802.11a: Up to 54Mbps 802.11b: Up to 11Mbps 802.11g: Up to 54Mbps 802.11n: Up to 172Mbps 802.11ac: Up to 433Mbps
	Antenna	1*1
	Users	16 users
Interface	SIM card	Single SIM card, hot plugging supported
	SIM card	NANO SIM card, eSIM optional
	USB	TYPE-C (USB2.0)
Button	Button	1*Power, 1*Reset
Charge	TYPE-C	5V/3A
Battery	Polymer battery	4400 mAh, could be customized.
Size	Size	125 x 70 x 17 mm (customized available)
Enviroment	Working Temperature	0°C-55°C
	StorageTemperature	-20°C-70°C
	Storage humidity	5%-95%

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518000

Email: [info@kingtoptec.com](mailto:info@kingtoptec.com)

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

\*Product specifications and availability are subject to change without notice.