

KINGTOP 4G Intelligent Printing Terminal Specification



Specifications

Basic configuration	Product Model	KT-V510
	CPU	ARM Cortex-A53 2.0GHz
	OS Version	Android™ 12.0
	RAM	2GB
	ROM	16GB
	2G/3G/4G Cellular	FDD-LTE:B1/B3/B5/B7/B8/B20/B26/B28 TDD-LTE:B38/B39/B40/B41 WCDMA:B1/B2/B5/B8 GSM/EDGE/GPRS: 850/900/1800/1900
LCM	LCD	5.5 inch (IPS), TFT-LCD, 720*1440 IPS
	Contrast ratio	Contrast > 600
	Brightness	300~380
	Touch Panel Material	G+FF
Camera	Front	2mp FF
	Rear	5mp AF
	1D/2D scanning	Support
Chip carrier	SIM card	Support, 1x SIM Card
	eSIM	Support(optional)
Wireless data	Wi-Fi	2.4G&5GHz, WIFI5: IEEE 802.11 ac/a/b/g/n
	Bluetooth	BT4.1 + BR/EDR + BLE
Connectivity	GNSS	Support GPS/GLONASS/AGPS
	NFC	Support 13.56MHz - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
	USB interface	Support TYPE-C, Micro USB v2.0, OTG
	Google GMS	Support
Audio	Speaker	1 x chamber horn, rated power 1W, loudness above 95dB
	MIC	Supports sound wave payment and recording

Port	PSAM	2*PSAM cradle, 1.8V/3.3V/5.0V
	POGOPIN	6 pin POGOPIN
	IC card	Not Support
	Magnetic stripe card	Not Support
	Printer	High speed thermal printer, paper roll width 58mm, paper roll diameter 40mm Speed:100mm/s
	Extend SD	TF Cards, up to 256GB
Accessories	Adaptor	DC: 5V/2A(optional)
	Cable	Type-C
	Printing paper	φ40*57mm
	Instructions	Support (including certificate of conformity and warranty card)
	Battery	7.6V/2500mAh
	Dimension	212 x 78 x 57 mm
Environment	Working Temperature	0°C-50°C
	Storage Temperature	-20°C-70°C
	Working Humidity	5%-95%

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.