KINGTOP

5G Body Worn Camera Specification



0 15 4						
Specificatio	ns					
	Product Model	KT-Z1				
	CPU	MTK-MT6877, 8-core processor, 6nm, 2.4GHz				
	Operating system	Android™11.0				
		Lens (mm)	Front	Rear		
	Lens	Lens type	GC5035 (5mp)	OS12D40 (11.3mp)		
		Angle of View (H)	70°(Horizontal 50°)	117°F/NO=2.2(Horizontal 105°)		
	SD Card	4+64GB (EMCP) standard, 6+128GB(optional)				
	TF Memory Card	Built in 64G(up to 256GB)				
	IR Light	2pcs OSRAM 850nm IR light (Face recognize feature within 3m) +1 pcs white light				
	TP	2.4 inch, 480*640, MIPI interface, capacitive touch screen				
Basic configuration	Speaker	8R/1.5W, 25*16mm IP68 dustproof and waterproof				
3	MIC	Dual MEMS MIC				
	Headphone	External Bluetooth intercom headset				
	5G wireless transferring (All Netcom)	2G: GSM B3/8 3G: WCDMA B1/8 4G: FDD-LTE B1/3/5/8 TDD-LTE B38/39/40/41 5G: N1/3/28/41/77/78/79				
	Antenna	6PCS (1T4R) +2 (Dual WIFI+GPS L1+L5 dual channel)				
	WIFI	802.11ac/a/b/g/n/ax,WIFI2.4, WIFI5.8, WIFI6				
	Bluetooth	BT5.1				
	External extension	9 pin contact interface for such NFC antenna interface, Serial port output interface				
	GNSS	GPS/Galileo/GLONASS/Beidou. Support GPS L1, L5 dual channel				
	Motion Sensor	6-axis gyroscope (for EIS electronic stabilization)				
Sensor	Magnetometer	eCompass automatically detects direction and orientation				
	Ambient light sensor	Support (Used to control the automatic opening and closing of IR lights)				
	Vibration motor	Support				
	Altitude Barometric Pressure Detection	Support				
Housing structure	Drop height	Meet the requirement of 2 meters, and any 4 surfaces accumulate 4 times				
	Housing Button	 Power button (Powering on and off) Video recording button (short press for video recording, long press for pre recording) Recording button (short press recording and long press to manually turn on the infrared light) Shutter button (short press to take a picture, long press to switch the recording resolution) SOS button (in normal mode, briefly press one button to play back, briefly press the button to mark the recording, and long press SOS recording) PTT button (long press intercom, release to answer) Menu button (single press to return, long press to turn on the white light) 				
	Button material	Silicon structure,Surface electroplating				
	L	1 - 1				

	Battery structure	Built-in replaceable batte	ery				
	Shutter	Electronic shutter					
	Continuous shooting	Support(App)					
Camera	Shake Reduction	Support (EIS ——electronic anti shake)					
	Focus distance	1m~ ∞					
	Digital zoom	Up to 16x					
	White balance	Auto					
	Photo size	up to100M					
Video	Video size	up to 4K*2K @30fps (3840*2160)					
	Pre/deferred recording	Prerecorded 1080P, max 30s The deferred time can be set by the menu (APP)					
	Shooting in Photography	Capture during the shooting process					
	Compressed format format	H.264/H.265					
	Image format	MP4					
		Standby	Recording	Charging			
	Status indicator (red/green/blue)	The status indicator is always on when standby, and it flashes red when recording	When recording, the status indicator flashes yellow (both red and green are on)	The indicator is blue when power up and charging, and the indicator is red when power off and charging			
	LED auxiliary lighting	White LEDs can be used	d for auxiliary lighting in da	ark situations			
	Playback video	When playing back video on your device, it supports dragging the progress bar on the touch screen					
	Highlights	Support					
	Watermark	MM-DD-YY-HHM					
Fuctions	Superimposed information	Equipment serial number+police information+Location information+time					
	Voice Announcements	Support(TTS voice broadcast)					
	Voice control	Support(Chinese)					
	Button response	<1s					
	Face recognition	After GPS is turned on, location information is superimposed on videos or photos					
	Motion detection	Support by APP					
	Voice cluster intercom	Support group, end-to-end intercom					
	Video intercom	Support one-way and two-way video intercom					
	OSD language	Chinese/English					
	Software update	Online update(APP)					
	External camera	Supports up to 1080P USB protocol cameras					
	External Battery	3300mAh/3.8V, -30 ℃ 1080P endurance ≥2 hours during low temperature environment					
	Built-in battery	65mAh (10C) /3.7V					
	Charging method	Adapter/PC-USB, vehicle USB					
Dattami	Charging time	<3 hour					
Battery	Recharging	≥500times					
	Usage time	9 hour (default)					
	Standby time	≥100 hours					
	Power saving mode	Support, it defaults to 30S and enters the power saving mode when there is no operation					
	Back clip	Support					
A	USB cable	TYPE-C, USB3.0					
Accessories	Charger	5V/2A, 5V/3A PD9V/2.22A, PE+9V/2A					
	Color box	Neutral					
	1	176.3g					
	Weight	176.3g					

General	Ingress Protection	IP68
	Operating Temperature	-30∼55℃
	Operating Humidity	40%~80%
	Storage temperature	-40~60°C
	Storage humidity	63%(30℃)

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com https://www.kingtoptec.com/

Copyrights © 2023 Kingtop Corp. All Rights Reserved

^{*}Product specifications and availability are subject to change without notice.