KINGTOP

5G Rugged tablet Specification



Specifications

Basic configuration	Product Model	KT-KP12
	OS Version	Android ™ 12.0
	CPU Type	MTK6891(MTK 1100), 6nm, 8 core, 3*Arm Cortex-A78@2.6GHz, 4*Arm Cortex-A55@2.0GHz
	Memory	6GB RAM+128GB ROM
Display	Screen	10.1" HD（1920*1200）
	Touch screen	Support (Multi-point touch)
	TP	Capacitive multi-touch screen G+FF
Network Connections	Bands	2.4G&5GHz,dual band
	Wi-Fi	Wi-Fi6, IEEE 802.11 a/b/g/n/ac/ax
	Bands	5G: N1/3/5/7/8/20/28/38/40/41/77/78/79 4G: TDD-LTE:B34/38/39/40/41; FDD-LTE:1/3/5/7/8/20/26/28A/28B;TD-SCDMA：B38/39/40/41 3G: WCDMA：B1/2/5/8; CDMA:BC0/BC1 2G: GSM：B2/3/5/8
	Data link	5G:NR 4G:TDD LTE FDD LTE 3G:HSPA+ ,EVDO ， GPRS EDGE; 2G:GPRS class 12/EDGEE
Camera	Front	8MP FF
	Rear	20MP AF
	Flashlight	Support
Speaker	Speaker	8R, 1W*2
	MIC	Support (Dual micro)
Sensor	G-sensor	Support(3D)
	Sensing distance	Support
	Compass	Support
	Motor	Support
	GPS	GPS/A-GPS/GLONASS/BEIDOU
Scan module	1D/2D	New land CM60
Connectivity	Bluetooth	BT5.1
	NFC	Support, 13.56MHz Contactlese interface modem - ISO/IEC 18000-3 、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
	OTG	Support
Button	Top	Power Button*1, Volume Button*2
	Left	Custom Button*2
Interface	SIM Card Slot	Dual cards(SIM+SIM or SIM+TF)
Battery	Capacity	8500mAh/3.8v

Accessories	Charger	DC 9V/2A
	Data cable	TYPE-C, 2.0
Others	Dimension	254.2*172.6*13.5mm
	Weight	830g
	Google GMS	Support
	Indicator light	Support, red light——charging, green light—— fully charged
Environment	Operating Temperature	-10℃-50℃
	Storage Temperature	-20℃-70℃
	Working Humidity	5%-95%
	Waterproof	IP67
	Explosion proof grade	Compatible Ex ib IIC T4 Gb

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051
Email: info@kingtoptec.com
https://www.kingtoptec.com/

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.