KINGTOP

5G Handheld Computer Specification



Specifications

Basic configuration	Product Model	**KT-KP26-5G**
	CPU	MT6877(MTK900),6nm, Octa core 2*A78 @2.4GHz,6*A55 @2.0GHz
	OS Version	Android11.0
	Memory	6GB RAM+128GB ROM
	Bluetooth	Bluetooth 5.1
LCM	LCD	6.217 inch (IPS), HD+，720*1520
	TP	Multi-touch, IC：GT911
	Cover plate material	Corning GG3, Reinforced glass cover plate, fully fitted, 1.1mm
Network	WLAN	Support 2.4/5GHz dual-band WIFI LAN 802.11 ax/ac/a/b/g/n, Wi-Fi 6
	Cellular data	4G:TDD LTE FDD LTE 3G:HSPA+ ,EVDO，GPRS EDGE; 2G:GPRS class 12/EDGEE 5G：NR
Sensor	GNSS	GPS/Beidou/Galileo/GLONASS/AGPS
	Motion Sensor	3-axis Accelerometer with MEMS Gyro
	Magnetometer	eCompass automatically detects direction and orientation
	Light Sensor	Automatically adjusts display backlight brightness
	NFC	Support, 13.56MHz Contactlese interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
Camera	Front	5mp FF
	Rear	13mp AF
	Rear secondary camera	5mp FF
	Flashlight	Support
Audio	Speaker	1W 8Ω*2，1217 dual speaker
	Headphone	Support 0809 IP68 waterproof
	Motor	0827 flat motor
	MIC	Dual MIC, 3D DNR MIC
IO interface	Earphone	Not support
	USB	Type-C USB2.0+charging, support OTG cable, 5V/2A
	SIM Card type	Dual cards(SIM+SIM or SIM+TF)
	TF card slot	Support TF card(up to 256GB)
Data Capture	Fingerprint module	Supuport fingerprint unlock, Interface:SPI, Sensor：FT9371L6, up to support five fingerprints
	Scan module	Newland CM60, support 1D/2D code
	Ray distance	Scanning distance up to 60cm/1.968 foot
Button	Left	Scan key * 1
	Right	On/Off key* 1+Volume key* 1+scan key * 1

Others	Google GMS	Support
	Battery	Removable battery, 5000mAh gel polymer , 4.35V (3.8V), 10K NTC resistance
	Dimension	168.3 x 79.5 x 16.9mm
	Certifications	3C certification, Drop test report,RoHS report
Accessories	Adaptor PE+	DC 5V/2A, 9V2A 18W flash charge
	Cable	Type-C USB2.0+charging
	Wrist strap	Optional
	Cradle	Optional
	Protect Shell	Optional
Environment	Operating Temperature	-20℃-60℃
	Storage Temperature	-40℃-70℃
	Working Humidity	5%-95%
	Drop Specifications	Multiple 1.5 m drops to tile over concrete
	Sealing	IP67

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

https://www.kingtoptec.com/

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.