KINGTOP

5G Mobile Hotspots Specification



Specifications

Basic configuration	Product Model	**KT-M4A**
	OS Version	Android™11.0
	Chipset	MTK MT6877(MTK900), 6nm, 2*A78（2.4GHz）+6*A55(2.0GHz), GPU：Mali OTR MC4
	Memory	LPDDR4X 2GB RAM+EMMC 32GB ROM
	WiFi	MT6635
	BT	Bluetooth 5.1(optional)
LCM	LED	1*5G signal, 1*4G signal, 1*Wifi, 1*Power
Cellular	Protocal	3GPP Rel.15，5G NR，SA/NSA，Sub 6G/LTE Category 18
	Bands	【EAU】 5G NR: N1/N3/N5/N7/N8/N20/N28/N40/N41/N77/N78 （N41/N77/N78 UL 2MIMO） 4G FDD: B1/B3/B5/B7/B8/B20/B28 4G TDD: B34/B38/B39/B40/B41 【LAM】 5G NR: N2*/N5/N8/N28/N40/N41/N66*/N77/N78 （N41/N77/N78 UL 2MIMO） 4G FDD: B2/B5/B7/B8/B28/B66
	Throughput	NR：Downlink/Uplink up to 2.77Gbps/1.25Gbps LTE：Downlink/Uplink up to 1.2Gbps/150Mbps WCDMA：Downlink/Uplink up to 42.2Mbps/11.5Mbps
	Antenna	4*4 MIMO
WiFi	Bands	2.4G, 5.8G, DBSC(2*2), DBDC（1*1）
	Protocal	802.11 a/b/g/n/ac/ax
	Throughput	802.11a：Up to 54Mbps 802.11b：Up to 11Mbps 802.11g：Up to 54Mbps 802.11n：Up to 300Mbps 802.11ac:Up to 866Mbps 802.11ax:Up to 1201Mbps
	Antenna	2*2
	Users	16 users
Interface	SIM card	Single SIM card, hot plugging supported
	SIM card	NANO SIM card, eSIM optional
	USB	TYPE-C（USB2.0）
Button	Button	1*Power, 1*Reset
Charge	TYPE-C	5V/2A
Battery	Polymer battery	4200 mAh, could be customized.
Size	Size	108.7x 68.2 x 16.2 mm
Environment	Working Temperature	0℃-45℃
	StorageTemperature	-20℃-70℃
	Storage humidity	5%-95%

Shenzhen Jintaiyi Electronic Co., Ltd.
12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 5
Email: info@kingtoptec.com
https://www.kingtoptec.com/
Copyrights © 2023 Kingtop Corp. All Rights Reserved
*Product specifications and availability are subject to change without notice.