KINGTOP

4G Mobile Hotspots Specification



Specifications

Basic configuration	Product Model	**KT-M6A**
	OS Version	Android™8.0
	Chipset	MTK MT6797
	Memory	3GB RAM+8GB ROM
	WiFi	MT6631
Display	LED	LCD or LED (Power,4G, 3G, Wifi)
Cellular	Protocal	3GPP Rel.11, LTE Category 6
	Bands	【EAU】 LTE-FDD: B1/B3/B5/B7/B8/B20/B28A LTE-TDD: B38/B40/B41 UMTS/HSPA/HSPA+: B1/B5/B8 【LAM】 LTE-FDD: B2/4/5/7/28/66 UMTS/HSPA/HSPA+: B1/2/4/5
	CA/ENDC	【EAU】 2CA DL 1A+5A/8A/20A/28A 3A+5A/8A/20A/28A 5A+5A/7A/40A 7A+7A/8A/20A/28A 20A+38A 40A+40A 41A+41A 【LAM】 2CA DL 2A+2A/4A/5A/66A 4A+4A/5A/28A 5A+5A/7A/66A 7A+7A/28A 66A+66A
	Throughput	LTE： Downlink/Uplink up to 300Mbps/50Mbps HSPA+：Downlink/Uplink up to 42.2Mbps/11.5Mbps
	Antenna	2*2 MIMO
WiFi	Bands	2.4GHz or 5GHz
	Protocal	802.11 a/b/g/n/ac
	Throughput	802.11n：Up to 150Mbps; 802.11ac: Up to 433Mbps
	Antenna	1*1
	Users	16 users
Interface	SIM card	Single SIM card, hot plugging supported
	USB	TYPE-C（USB2.0）
General	Button	1*Power, 1*Reset
	TYPE-C	5V/2A
	Polymer battery	3000 mAh
	Dimension	108.7x 68.2 x 16.2 mm
Environment	Operating Temperature	0℃-45℃
	StorageTemperature	-20℃-70℃
	Working humidity	5%-95%

Shenzhen Jintaiyi Electronic Co., Ltd.
12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 5
Email: info@kingtoptec.com
https://www.kingtoptec.com/
Copyrights © 2023 Kingtop Corp. All Rights Reserved
*Product specifications and availability are subject to change without notice.